


|  BY PRONESA Screw Air Compressor | |
|---|------------------------|
| Model | ATD-150A |
| Air flow (CFM) | 692 |
| Working pressure (PSI) | 125 |
| Power(KI/WHP) | 110/150 |
| Electricity(V/ph/Hz) | 460V 3PH 60HZ |
| Starting Mode | Y-Δ starting |
| No. of compression stage | Single stage |
| Ambient temperature(°C) | -5~+45 |
| Oil separator tank | ASME certificate |
| Cooling model | Air cooling |
| Housing Materials Of Filter | Aluminium |
| Service Life Of Filter Elements(hours) | 3000 hours |
| Discharge temperature(°C) | Ambient temperature+15 |
| Lubricant(L) | 75 |
| Noise level(Db) | 70-74 |
| Drive method | Direct drive |
| Dimension:L*W*H(mm) | 2500*1450*1800 |
| Weight(kg) | 2150 |

JUAN ZUAZUA NO.200
 COLLAZARO CARDENAS AMPLIACION
 GENERAL ESCOBEDO, N.L. C.P.68058
 TEL: (81) 83-73-88-99
www.airturbo.com.mx

| | | | | |
|-------------------|--|--|--|--|
| FECHA : 20/7/2020 | | | | |
| ACOTACIONES : MM | | | | |
| | | | | |
| | | | | |



BY PRONESA