


|  BY PRONESA Screw Air Compressor | |
|---------------------------------------------------------------------------------------------------------------------------|------------------------|
| Model | ATD-75A |
| Air flow (CFM) | 316 |
| Working pressure (PSI) | 125 |
| Power (KW/HP) | 55/75 |
| Electricity (V/Ph/Hz) | 460V 3Ph/60Hz |
| Starting Mode | Y-Δ starting |
| No of compression stage | Single stage |
| Ambient temperature (°C) | -5~+45 |
| Oil separator tank | ASME certificate |
| Cooling model | Air cooling |
| Housing Material: Of Filter | Aluminium |
| Service Life Of Filter Elements (hours) | 3000 hours |
| Discharge temperature (°C) | Ambient temperature+15 |
| Lubricant (L) | 45 |
| Noise level (Db) | 70-74 |
| Drive method | Direct drive |
| Dimension L*W*H (mm) | 1800*1070*1490 |
| Weight (kg) | 1100 |

JUANZ UZ UANO,200
 COL LAZARO CARDENAS AMPLIACION
 GENERAL ESCOBEDO, N.L. CP 66058
 TEL: (81) 83-73-88-99
www.airturbo.com.mx

| | | | | | |
|-------------------|--|--|--|--|--|
| FECHA : 20/7/2020 | | | | | |
| ACOTACIONES : MM | | | | | |
| | | | | | |
| | | | | | |



BY PRONESA